



# GATOR WRAP

## *Infi-Shield® External Gator Wrap*

**Infi-Shield® Gator Wrap prevents infiltration by providing a water-tight seal around any manhole, catch basin or concrete pipe joint. Gator Wrap resists harsh soil conditions and also provides a root barrier for any crack or joint. Infi-Shield® Gator Wrap installs easily with no special tools and can be immediately backfilled.**

**EPDM Rubber Specifications  
Material Meets: ASTM C877 Type III  
and C923**



### **Infi-Shield® Gator Wrap Specification**

Each manhole, catch basin or pipe joint shall be sealed with an external rubber sleeve similar to the Infi-Shield Gator Wrap as manufactured by Sealing Systems Inc (763-478-2057). The seal shall be made of a Stretchable, Self-Shrinking, Intra-Curing Halogenated based rubber with a minimum thickness of 30 mils. The back side of each unit shall be coated with a cross-linked re-enforced butyl adhesive. The butyl adhesive shall be non-hardening sealant with a minimum thickness of 30 mils. The seal shall be designed to stretch around the joint and then overlapped creating a cross-link and fused bond between the rubber and butyl adhesive. Gator Wrap forms a continuous rubber seal on a manhole joint which prevents water and soil from infiltrating through the manhole, catch basin or concrete pipe joint.

INFI-SHIELD Gator Wrap® is available in 6" and 9" widths and comes in a 50 foot roll or in a user-friendly kit which has six sixteen foot rolls. Gator Wrap® is also available in a 12" width by 50 foot roll.

Physical Properties	ASTM Test Method	Test Results
Hardness	D2240 (60 min-70 max)	Pass
Tensile, PSI	D412 (1204 psi min.)	Pass
Compression Set	D395 25% max deflection	Pass
Low Temperature	D2137 No fracture @ -40 C	Pass
Heat Aging	D573 96 hrs @ 158° F	Pass
Water Absorption	D471 48 hrs @ 158° F (10% max)	Pass
Elongation %	D412 (350% min. @ break)	Pass
Ozone Resistance	D1149 and D1171	Pass
Tear Resistance	D624 die B (5 psi min.)	Pass

**Disclaimer:** This technical data information and recommendations offered are based on independent lab test results, and findings we believe to be reliable and complete.



**Sealing Systems, Inc.**

9350 County Road 19 ♦ Loretto, MN 55357 ♦ 763-478-2057 ♦ 800-478-2054 ♦ Fax 763-478-8868 ♦ [www.infi-shield.com](http://www.infi-shield.com)



# GATOR WRAP

## INSTALLATION INSTRUCTIONS



1. Expose the area that is to be sealed. Clean the entire area around the joint with a wire brush and whisk broom. Remove any sharp protruding edges around the joint with an abrasive tool. When finished cleaning, the entire area must be dry and free of any dirt.



2. Remove the first foot of paper backing from the mastic. Center and place the Gator Wrap® around the joint. Continue to remove paper backing as you apply the Gator Wrap to the entire structure.



3. Seal the overlapping area with a 6" overlap. Be sure not to stretch material at the overlap area.



4. Cut excess material using a utility knife. Using a rubber mallet or hand held roller, firmly flatten the Gator Wrap® 360 degrees around joint.



Sealing Systems, Inc.