



**ONE** coupling per nominal diameter joins:

Clay    Cast Iron    Plastic  
Ductile Iron    Asbestos Cement

For non-pressure, gravity flow sewer applications only.

SIZE	PART DESCRIPTION	O.D. RANGE
4"	MAX 4	4.13" - 5.56"
5"	MAX 5	5.30" - 6.50"
6"	MAX 6	6.27" - 7.75"
6"+	MAX 6 Oversize	6.27" - 8.10"
7"	MAX 7	7.20" - 8.80"
8"	MAX 8	8.40" - 10.15"
9"	MAX 9	9.63" - 11.13"
10"	MAX 10	10.50" - 12.68"
12"	MAX 12	12.50" - 15.00"
13"	MAX 13	13.00" - 15.75"
16"	MAX 16	16.34" - 19.10"

U.S. Patent Nos. US 8,651,532 B2 & US 8,635,747 B2

Gripper Gasket LLC  
1660 Leeson Lane | Corona, CA 92879  
(951) 479-4999 | (951) 479-4997 Fax

[maxadaptor.com](http://maxadaptor.com)

Rev. 08/20



**STOP THE  
GUESSWORK**



**The Only Universal  
Sewer Repair  
Coupling**

[maxadaptor.com](http://maxadaptor.com)

# 20 ADVANTAGES at a GLANCE

